Description

Heterogeneous indoor floorcovering, 3.45mm thick.

1: DANCER-APPROVED SURFACE FRICTION

Dancefloor is backed with an engineered surface texture providing optimal friction and light reflection 2: DYNAMIC COLOURS AND REALISTIC DECORS

- High definition printing for higher colour intensity 3: OUTSTANDING DIMENSIONAL STABILITY < 0.10%:
- Extremely tough single glass veil reinforcement
- 4: HIGH PERFORMANCE AND DURABILITY: Homogeneous calendared sheet made from up to 60% recycled vinyl.

5: COMFORT, SAFETY AND BOOSTED SPORTS EXPERIENCE:

High-density closed-cell foam with engineered honeycomb backing.



PROPERTIES	STANDARDS	DANCEFLOOR
DECLARATION OF PERFO	RMANCE	
	0120-081-DoP-2019-02	
CLASSIFICATION		
Type of floor covering	EN 14041	Heterogeneous indoor floorcoverings
TECHNICAL CHARACTER	ISTICS	
Total thickness	ISO 24346 (EN 428)	3.45mm
Total weight	ISO 23997 (EN 430)	3040g/m ²
Width	ISO 24341 (EN 426)	2m
₋ength	ISO 24341 (EN 426)	15lm
REQUIREMENTS FOR SAI	FE USE	
Friction	EN 13036-4	≥90
Shock absorption	EN 14808	≥4%
		-
Vertical deformation	EN 14809	≤0.8mm
Specular gloss	EN ISO 2813	≤30
TECHNICAL PERFOMANC	CES	
/ertical ball behaviour	EN 12235	
Reaction to fire	AS/ISO 9239-1	Critical radiant flux 8.6 kW/m ² Smoke 186%. min
Resistance to wear	EN ISO 5470-1	≤1g
Resistance to indentation	Average measured value	≤0.18mm
	EN 1516	≤0.50mm
Resistance to a rolling load	EN 1569	-
n room noise	NFS-074	Class A ≤65dB
Thermal resistance	EN ISO 14456	Approx. 0.05 m² K/W
		Compatible with underfloor heating

Colors available



* glued installation on concrete

Installation and maintenance guides available on request

Technical data in force as from the date of publication (1/2/2022). The values above correspond to laboratory test (no in situ test), and are subject to modifications for the benefit of further improvement. For more detailed technical information, please contact Tarkett.

Colors of the products shown in the photos or samples are indicative only. There may be differences in color, gloss and embossing structure between the products sold and photos or samples.

